


**ARQ SYSTEM**

**Publication number:** JP60041832 (A)  
**Publication date:** 1985-03-05  
**Inventor(s):** IWAMORI TAKUO; FUJIWARA TOSHIYUKI +  
**Applicant(s):** JAPAN RADIO CO LTD; BOEICHO GIJUTSU KENKYU HONBUCH +  
**Classification:**  
- **international:** **H04L1/00; H04L1/16; H04L1/00; H04L1/16;** (IPC1-7): H04L1/16  
- **European:** H04L1/00B5L; H04L1/16F  
**Application number:** JP19830150025 19830817  
**Priority number(s):** JP19830150025 19830817

**Abstract of JP 60041832 (A)**

**PURPOSE:** To attain retransmission request in block unit or bit unit by applying decoding of data by means of the maximum likelihood method at the data reception side and utilizing a likelihood function or a likelihood function difference calculated in the decoding as the decision of the retransmission request. **CONSTITUTION:** A signal transmitted from a data transmitter 4 is received by a receiver 6 and given to a maximum likelihood decoder 7 of the next stage at the reception side. The maximum likelihood decoder 7 operates the likelihood function based on a prescribed formula, compares the level and outputs the largest likelihood function among the likelihood functions and a data corresponding thereto to a deciding device 8. The device 8 compares the likelihood function outputted from the maximum likelihood decoder 7 with a predetermined deciding level. When the inputted likelihood function is larger than the deciding level in this case, the inputted data is stored in a prescribe address of a data buffer 9, and when the inputted data is smaller than the deciding level, the address of the inputted data is transmitted to the data transmission side via a transmitter 10 as a retransmission request signal.



.....  
Data supplied from the **espacenet** database — Worldwide